



CARE MANUAL

MADEPLAST

MADEPLAST

PLEASE READ CAREFULLY ALL THE INFORMATION CONTAINED IN THIS MANUAL TO ENSURE THAT YOUR MADEPLAST PRODUCT HAS ITS BENEFITS PRESERVED.

1

GENERAL INFORMATION

Following the instructions contained in this manual will help in the correct cleaning and conservation of the product, guaranteeing that all the characteristics and benefits of WPC MADEPLAST are preserved.

Once the WPC MADEPLAST product has been installed, the area must be cleaned. In addition, all residues and leftovers must be collected, including unused screws, as they could scratch the surface of the pieces.

It is best to complete the cleaning early in the morning or in the evening when the surface is cool, to prevent cleaners from drying or evaporating on the pieces. Understanding the instructions certifies the durability of the pieces, structures, and other finishes of the MADEPLAST materials.

2

SURFACE CLEANING RECOMMENDATIONS

- The cleaning of the MADEPLAST products is simple: just use water and neutral soap.
- No type of solvent or corrosive product should be used for cleaning, as it can cause stains on the product.
- Periodic maintenance is recommended, such as the cleaning of dust, leaves, organic debris or other materials that obstruct the proper ventilation of WPC MADEPLAST, including the spacing between the pieces, if any.
- The accumulation of dirt or particularly aggressive contaminants can cause superficial stains, apart from causing aesthetic damage to the product.



MADEPLAST

3

DEEP CLEANING RECOMMENDATIONS

- For deeper cleaning, pressure machines with non-directional water jets can be used. The maximum recommended pressure is 1500 psi. Follow the finishing direction of the MADEPLAST pieces and use a nozzle with a fan opening greater than 14 cm, 45° angle and distance greater than 30 cm.



WARNING: misuse of high water pressure can result in irreparable damage. Be careful not to damage the material and take the necessary safety measures.



For difficult cleaning, we recommend the use of 96° GL alcohol diluted in water and soaked in a soft cloth, taking care during cleaning not to cause abrasion of the MADEPLAST products.

Failure to clean the WPC MADEPLAST products as recommended in this manual can permanently stain the product and, in such case, it is recommended to sand the part.

For more technical information, see documents and manuals available at madeplast.com.br



MADEPLAST

MADEPLAST INDÚSTRIA E COMÉRCIO DE MADEIRA PLÁSTICA LTDA.
CNPJ: 10.278.073/0003-65 - Av. Taurus, nº 40 (Rod. BR 116, km 137) - CIMAN
CEP: 83800-000 - POSTAL BOX: 13058 - Mandirituba - Parana - Brazil
Phone: (41) 3045-4050 / (41) 3633-1880
Site: madeplast.com.br